




BW0404

Fasson®
PE45 White NTC/
S692N/BG40#WH Imp

Fasson® PE45 White NTC is A corona treated white polyethylene film with medium gloss appearance.

Applications



Key Features

> Designed for application on Fruit Label

Facestock

A corona treated white polyethylene film with medium gloss appearance.

Basis Weight: 44 g/m2± 10% ISO536 Caliper: 0.045 mm ± 10% ISO534

Adhesive

A general purpose permanent, acrylic based adhesive.

Line

A super calendared white glassine paper with excellent roll label converting properties.

Basis Weight: 62 g/m2 10% ISO536 Caliper: 0.055mm 10% ISO534

Performance data

Loop Tack (st,st)-FTM 9: 9.5 20 min 90 Peel (st,st)-FTM 2: 5.5 24 hour 90 Peel (st,st)-FTM 2: 8.0 Minimum Application Temperature: -5C Service Temperature Range: -29C~+93C

Adhesive Performance

It is a clear permanent adhesive designed for prime labeling applications including squeezable and clear labeling applications. Specifically designed to exhibit excellent wet-out characteristics on clear films.

It is suitable for applications where compliance with FDA 175.105 is required. This section covers applications where for indirect contact food, or incidental contact cosmetic or drug products.

Applications and use

Due to its flexibility the product is especially suitable for Firut Label like apple banana and pear.

Labeling testing is always recommended for rough surface.

Conversion/printing

The corona treated face material can be printed by letterpress, flexo, giving good print results with UV curing and water based inks.

To ensure optimum wettability and ink bond, additional in-line corona treatment is required.

Ink testing is always recommended before production.


Sharp film tooling preferably in flat-bed, are important to ensure smooth conversion.


Acceptance of hot stamping foil is excellent.

Need avoid too much re-winding tension to causing bleeding.

Shelf life

Fasson[®] PE45 White NTC/S692N/ BG40#WH Imp





Asia Pacific

32/F., Skyline Tower 39 Wang Kwong Road Kowloon Bay, Kowloon, Hong Kong Tel: +852 2802-9618

Warrenty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do no constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsable for claims beyond the replacement value of the defective product or in any way

liable or responsable for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTIBILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERNATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.